





# FICHA TECNICA



Producto	:	Selector M-O-A
Marca	:	CNC
Modelo	:	<b>EP-16A-M</b>
Amps	:	16A
Polos	:	1
Certificac.	:	   



AC Rating Code	Unit	S16/TP16/ RT16	
Rated Operational Voltage(Ue)	V	690	
Rated frequency	Hz	50/60	
Rated impulse withstand Voltage(Uimp)	Kv	6	
Rated Operational Current(Ie) AC21/AC1	A	16	
Rated Uninterrupted Current (Ith)	A	20	
Rated Operational Power			
AC23A "3 Ph , 415 V"	KW	7.5	
	A	13	
AC3	KW	5.5	
"3 Ph , 415 V"	A	10	
Short Circuit Capacity			
Rated Fuse Short Circuit Current	KA	5	
Fuse Size (Type gG/gM)	A	16	
Terminal Cross Section			
Single / Multiple	min	mm <sup>2</sup>	1.5
	max	mm <sup>2</sup>	4
Fine strand	min	mm <sup>2</sup>	1
	max	mm <sup>2</sup>	2.5
Terminal Cross Section	Metric	M3.5	
Terminal Tightening Torque	Nm	0.8	

## CSA/UL Ratings

AC Rating Code	Unit	S16 TP16 RT16
<b>Ampere Rating</b>	A	15
Operational Voltage	V	600
HP Rating 1 Phase 120V	HP	0.33
240V	HP	1
3 Phase 120V	HP	1.5
240V	HP	3
480V	HP	3
600V	HP	5

