



# YS29, Cu Compression Splice, Long Barrel, 250 kcmil

By Burndy  
Catalog # [YS29](#)

250 kcmil, CU, Long Barrel SPLICE

## Features

- Copper seamless barrel with center stop indentations to indicate when wire is fully inserted into each side of the barrel
- Electro-tin plated unless otherwise specified to reduce galvanic corrosion (bimetallic) and resist corrosive elements
- Connectors clearly marked with color coding

## Application

Wire Splice

## Specifications

Buy American Compliant	Contact Manufacturer
EU RoHS Indicator	Yes
Industry Standard(s)	UL 486A-486B
Buy America(n) Qualified	TAA Compliant (All status valid till December 2026)
Standards - Industry Standards Met	UL 486A-486B
Standards - RoHS Compliance Status	CM
Certification - CSA Approved	Yes
UL Listed	Yes

## Conductor

Conductor - Material	COPPER
Wire Size	250 kcmil
Conductor - Copper Str Size	250 kcmil
Conductor - Copper Str Navy Size	250 (61) Navy
Conductor Size	250 KCMIL
Conductor - Copper Str Size Range	250 kcmil
Conductor Type	CODE

## Configuration

Connector Type	LONG BARREL
----------------	-------------

## Current

Voltage - Maximum	35000
Voltage Rating	35 kV

## Dimensions

Package Length	0.000 in
Package Width	0.000 in
Package Weight	0.000 lb.
Dimension - L Length Overall mm	91 mm
Package Height	0.000 in
Dimension - Strip Length inch	1-11/16
Dimension - B Length inch	1.58 in
Dimension - Length Overall inch	3.58 in

## General

Die Index	16
Trade Name	HYLINK™
Sub Brand	HYLINK
Color Code	Yellow
Plated	Y
Feature - Barrel Type	Long
Feature - Barrel Style	Chamfered
Type	YS, Long Barrel
UPC 12 Digit	781810507957
UPC 14 Digit GTIN	00781810507957
Material	COPPER
Plating Type	Tin - Electro Plated
Finish Type	Tin-Plated
UPC	781810507957

## Logistics

Minimum Pack Quantity	1
Carton Quantity	10

## Product Assets

[Catalog \[English\]](#)