



YHD200, Compression Line Tap, CU, AL, ACSR, Compact

By Burndy
Catalog # [YHD200](#)



Compression Line Tap for Copper, AL or ACSR and Compact Conductors, wire diameter range, groove A(Run):0.398-0.470

Features

- Wide range, Universal and Reversible Figure H Shapped aluminum compression connector
- Bendable tabs secure both run and tap conductors freeing the installers hands to work with the installation tool
- Massive aluminum design minimizes corrosion due to galvanic corrosion
- Pre-filled with PENETROX Joint Compound and individually packaged
- Conductor ranges and tooling is clearly printed on connector and package

Application

For Copper, Aluminum Or ACSR And Compact Conductors

Specifications

| | |
|------------------------------------|---|
| Buy American Compliant | Contact Manufacturer |
| Certification - cULus | No |
| EU RoHS Indicator | Yes |
| Certification - UL Recognized | No |
| Buy America(n) Qualified | TAA Compliant (All status valid till December 2026) |
| Certification - ETL | No |
| Standards - RoHS Compliance Status | CM |
| Certification - CSA Approved | No |
| UL Listed | No |

Conductor

| | |
|---------------------------------|---|
| Conductor - ACSR Cmpt Run | <ul style="list-style-type: none"> • 2/0 AWG • 3/0 AWG |
| Conductor - ACSR Cmpt Run Range | 2/0 AWG-3/0 AWG |
| Conductor - ACSR Cmpt Tap | <ul style="list-style-type: none"> • 6 AWG • 4 AWG • 3 AWG • 2 AWG • 1 AWG |
| Conductor - ACSR Cmpt Tap Range | 6 AWG-1 AWG |
| Conductor - ACSR Str Run | <ul style="list-style-type: none"> • 1/0 (6/1) Raven AWG • 2/0 (6/1) Quail AWG |
| Conductor - ACSR Str Run Range | 1/0 (6/1) Raven AWG-2/0 (6/1) Quail AWG |
| Conductor - ACSR Str Tap | <ul style="list-style-type: none"> • 6 (6/1) Turkey AWG |

- 5 (6/1) Thrush AWG
- 4 (6/1) Swan AWG
- 4 (7/1) Swanate AWG
- 3 (6/1) Swallow AWG
- 2 (6/1) Sparrow AWG
- 2 (7/1) Sparate AWG

| | |
|------------------------------------|---|
| Conductor - ACSR Str Tap Range | 6 (6/1) Turkey AWG-2 (7/1) Sparate AWG |
| Conductor - AL Str Run | 3/0 - 4/0 |
| Conductor - AL Str Run Range | 3/0 - 4/0 |
| Conductor - AL Str Tap | <ul style="list-style-type: none"> • 6 AWG • 4 AWG • 3 AWG • 2 AWG • 1 AWG |
| Conductor - AL Str Tap Range | 6 AWG-1 AWG |
| Conductor - Copper Solid Run | <ul style="list-style-type: none"> • 3/0 AWG • 4/0 AWG |
| Conductor - Copper Solid Run Range | 3/0 AWG-4/0 AWG |
| Conductor - Copper Solid Tap | <ul style="list-style-type: none"> • 6 AWG • 5 AWG • 4 AWG • 3 AWG • 2 AWG • 1 AWG • 1/0 AWG |
| Conductor - Copper Solid Tap Range | 6 AWG-1/0 AWG |
| Conductor - Copper Str Run | <ul style="list-style-type: none"> • 2/0 AWG • 3/0 AWG |
| Conductor - Copper Str Run Range | 2/0 AWG-3/0 AWG |
| Conductor - Copper Str Tap | <ul style="list-style-type: none"> • 6 AWG • 5 AWG • 4 AWG • 3 AWG • 2 AWG • 1 AWG |
| Conductor - Copper Str Tap Range | 6 AWG-1 AWG |

Dimensions

| | |
|----------------|-----------|
| Package Length | 0.000 in |
| Package Width | 0.000 in |
| Package Weight | 0.000 lb. |

Dimension - L Length Overall mm 41 mm
Dimension - Height fraction 1-11/25 in
Dimension - Height inch 1.45 in
Package Height 0.000 in
Dimension - Height mm 36.8 mm
Dimension - Width inch 0.89 in
Dimension - Width mm 23 mm
Dimension - Length Overall inch 1.62 in

General

Die Index D3
Trade Name HYCRIMP™
Prefilled Oxide Inhibitor Y

Sub Brand HYCRIMP
Plated N
Type YHD
UPC 14 Digit GTIN 00781810139158
Material Aluminum
Plating Type Unplated
UPC 781810139158

Logistics

Minimum Pack Quantity 25
Carton Quantity 250
Pallet Quantity 8250

Product Assets

[Catalog \[English\]](#)



A Hubbell brand