

YHD300, Line Tap, Cu, AL, ACSR, Compact

By Burndy
Catalog # YHD300

Compression Line Tap for Copper, AL or ACSR and Compact Conductors, wire diameter range- groove A(Run): 0.336 - 0.470



Features

- Wide range, Universal and Reversible Figure H Shapped aluminum compression connector
- Bendable tabs secure both run and tap conductors freeing the installers hands to work with the installation tool
- Massive aluminum design minimizes corrosion due to galvanic corrosion
- Pre-filled with PENETROX Joint Compound and individually packaged
- Conductor ranges and tooling is clearly printed on connector and package

Application

For Copper, Aluminum Or ACSR And Compact Conductors

Specifications

Buy American Compliant	Yes
Certification - cULus	No
EU RoHS Indicator	Yes
Certification - UL Recognized	No
Buy America(n) Qualified	<ul style="list-style-type: none"> • Buy America Compliant (All status valid till December 2025) • Buy American Act Compliant (All status valid till December 2025) • BABA Compliant (All status valid till December 2025)
Certification - ETL	No
Standards - RoHS Compliance Status	CM
Certification - CSA Approved	No
UL Listed	No

Conductor

Conductor - ACSR Cmpt Run	<ul style="list-style-type: none"> • 1/0 AWG • 2/0 AWG
Conductor - ACSR Cmpt Run Range	1/0 AWG-2/0 AWG
Conductor - ACSR Cmpt Tap	<ul style="list-style-type: none"> • 1/0 AWG • 2/0 AWG • 3/0 AWG
Conductor - ACSR Cmpt Tap Range	1/0 AWG-3/0 AWG
Conductor - ACSR Str Run	• 1 (6/1) Robin AWG

Conductor - ACSR Str Run Range	<ul style="list-style-type: none"> • 1/0 (6/1) Raven AWG • 2/0 (6/1) Quail AWG
Conductor - ACSR Str Tap	<ul style="list-style-type: none"> • 1 (6/1) Robin AWG-2/0 (6/1) Quail AWG • 1 (6/1) Raven AWG • 2/0 (6/1) Quail AWG
Conductor - ACSR Str Tap Range	1 (6/1) Raven AWG-2/0 (6/1) Quail AWG
Conductor - AL Str Run	2/0 - 4/0
Conductor - AL Str Run Range	2/0 - 4/0
Conductor - AL Str Tap	<ul style="list-style-type: none"> • 1 AWG • 1/0 AWG • 2/0 AWG
Conductor - AL Str Tap Range	1 AWG-2/0 AWG
Conductor - Copper Solid Run	<ul style="list-style-type: none"> • 2/0 AWG • 3/0 AWG • 4/0 AWG
Conductor - Copper Solid Run Range	2/0 AWG-4/0 AWG
Conductor - Copper Solid Tap	<ul style="list-style-type: none"> • 2/0 AWG • 3/0 AWG
Conductor - Copper Solid Tap Range	2/0 AWG-3/0 AWG
Conductor - Copper Str Run	<ul style="list-style-type: none"> • #1(3) • 2 AWG • 1 AWG • 1/0 • 2/0 AWG • 3/0
Conductor - Copper Str Run Range	#1(3)-3/0
Conductor - Copper Str Tap	<ul style="list-style-type: none"> • 2/0 AWG • 3/0 AWG
Conductor - Copper Str Tap Range	2/0 AWG-3/0 AWG

Dimensions

Package Length	0.000 in
Package Width	0.000 in
Package Weight	0.000 lb.
Dimension - L Length Overall mm	41 mm
Dimension - Height fraction	1-21/50 in
Dimension - Height inch	1.42 in
Package Height	0.000 in
Dimension - Height mm	36.1 mm

Dimension - Width fraction 89/100 in
Dimension - Width inch 0.89 in
Dimension - Width mm 23 mm
Dimension - Length Overall 1.62 in
inch

UPC 14 Digit GTIN 00781810139257
Material Aluminum
Plating Type Unplated
UPC 781810139257

General

Die Index D3
Trade Name HYCRIMP™
Prefilled Oxide Inhibitor Y
Sub Brand HYCRIMP
Plated N
Type YHD

Logistics

Minimum Pack Quantity 25
Carton Quantity 250
Pallet Quantity 8250

Product Assets

[Catalog \[English\]](#)



A Hubbell brand