

YHO150, Aluminum Overhead Tap Connector, AL, CU, ACSR, AAAC, Steel

By Burndy
Catalog # [YHO150](#)



AL Overhead Compression Tap Connector, Accommodates: AL, CU, ACSR, AAAC and Steel, Length: 1.50 IN

Features

- Wide range, Universal and Reversible Figure H Shapped aluminum compression connector
- Bendable tabs secure both run and tap conductors freeing the installers hands to work with the installation tool
- Massive aluminum design minimizes corrosion due to galvanic corrosion
- Pre-filled with PENETROX Joint Compound and individually packaged
- Conductor ranges and tooling is clearly printed on connector and package

Application

For Copper, Aluminum Or ACSR And Compact Conductors

Specifications

| | |
|------------------------------------|---|
| Buy American Compliant | No |
| Certification - cULus | No |
| EU RoHS Indicator | Yes |
| Certification - UL Recognized | No |
| Buy America(n) Qualified | TAA Compliant (All status valid till December 2026) |
| Certification - ETL | No |
| Standards - RoHS Compliance Status | CM |
| Certification - CSA Approved | No |
| UL Listed | No |

Conductor

| | |
|---------------------------------|--|
| Conductor - ACSR Cmpt Run | <ul style="list-style-type: none"> • 2 AWG • 1 AWG • 1/0 AWG |
| Conductor - ACSR Cmpt Run Range | 2 AWG-1/0 AWG |
| Conductor - ACSR Cmpt Tap | <ul style="list-style-type: none"> • 6 AWG • 4 AWG • 3 AWG • 2 AWG • 1 AWG |
| Conductor - ACSR Cmpt Tap Range | 6 AWG-1 AWG |
| Conductor - ACSR Str Run | <ul style="list-style-type: none"> • 3 (6/1) Swallow AWG • 2 (6/1) Sparrow AWG • 2 (7/1) Sparate AWG • 1 (6/1) Robin AWG |

| | |
|------------------------------------|--|
| Conductor - ACSR Str Run Range | <ul style="list-style-type: none"> • 1/0 (6/1) Raven AWG 3 (6/1) Swallow AWG-1/0 (6/1) Raven AWG |
| Conductor - ACSR Str Tap | <ul style="list-style-type: none"> • 6 (6/1) Turkey AWG • 5 (6/1) Thrush AWG • 4 (6/1) Swan AWG • 4 (7/1) Swanate AWG • 3 (6/1) Swallow AWG • 2 (6/1) Sparrow AWG • 2 (7/1) Sparate AWG |
| Conductor - ACSR Str Tap Range | 6 (6/1) Turkey AWG-2 (7/1) Sparate AWG |
| Conductor - AL Str Run | #1 - 2/0 |
| Conductor - AL Str Run Range | #1 - 2/0 |
| Conductor - AL Str Tap | <ul style="list-style-type: none"> • 6 AWG • 4 AWG • 3 AWG • 2 AWG • 1 AWG |
| Conductor - AL Str Tap Range | 6 AWG-1 AWG |
| Conductor - Copper Solid Run | <ul style="list-style-type: none"> • 1 AWG • 1/0 AWG • 2/0 AWG |
| Conductor - Copper Solid Run Range | 1 AWG-2/0 AWG |
| Conductor - Copper Solid Tap | <ul style="list-style-type: none"> • 6 AWG • 5 AWG • 4 AWG • 3 AWG • 2 AWG • 1 AWG • 1/0 AWG |
| Conductor - Copper Solid Tap Range | 6 AWG-1/0 AWG |
| Conductor - Copper Str Run | <ul style="list-style-type: none"> • 3 AWG • 2 AWG • 1 AWG • 1/0 • 2/0 AWG |
| Conductor - Copper Str Run Range | 3 AWG-2/0 AWG |
| Conductor - Copper Str Tap | <ul style="list-style-type: none"> • 6 AWG • 5 AWG • 4 AWG • 3 AWG • 2 AWG • 1 AWG |

Conductor - Copper Str Tap Range 6 AWG-1 AWG

Dimensions

| | |
|---------------------------------|-----------|
| Package Length | 0.000 in |
| Package Width | 0.000 in |
| Package Weight | 0.000 lb. |
| Dimension - L Length Overall mm | 38 mm |
| Dimension - Height fraction | 1-3/25 in |
| Dimension - Height inch | 1.13 in |
| Package Height | 0.000 in |
| Dimension - Height mm | 28.7 mm |
| Dimension - Width fraction | 7/10 in |
| Dimension - Width inch | 0.70 in |
| Dimension - Width mm | 18 mm |
| Dimension - Length Overall inch | 1.50 in |

General

| | |
|---------------------------|----------------|
| Die Index | O |
| Trade Name | HYCRIMP™ |
| Prefilled Oxide Inhibitor | Y |
| Sub Brand | HYCRIMP |
| Plated | N |
| Type | YHO |
| UPC 14 Digit GTIN | 00781810139103 |
| Material | Aluminum |
| Plating Type | Unplated |
| UPC | 781810139103 |

Logistics

| | |
|-----------------------|-------|
| Minimum Pack Quantity | 25 |
| Carton Quantity | 350 |
| Pallet Quantity | 11550 |

Product Assets

[Catalog \[English\]](#)



A Hubbell brand

© 2026 Hubbell Incorporated. All rights reserved
BRDY-YHO150-SPEC-EN | REV 4/2026