



UT136C+



Specifications	Range	UT136B+	UT136C+
DC voltage (V)	1000V	±(0.7%+3)	±(0.7%+3)
AC voltage (V)	1000V	±(1%+3)	±(1%+3)
DC current (A)	10A	±(1%+3)	±(1%+3)
AC current (A)	10A	±(1.2%+5)	±(1.2%+5)
Resistance (Ω)	40MΩ	±(0.8%+2)	±(0.8%+2)
Capacitance (F)	40mF	±(3%+5)	±(3%+5)
Frequency (Hz)	400Hz~40MHz	±(0.1%+4)	±(0.1%+4)
Temperature (°C)	-40~1000°C		±(1%+3)
Temperature (°F)	-40~1832°F		±(1.5%+5)
Display count		4000	4000
NCV		v	
Category ratings	CAT II 1000V, CAT III 600V		

### Features

Equipped with 3mm protective sleeve	Measures up to 1000V and 10A AC/DC current
Quick sampling rate, up to 4 times/s	Large LCD display
Transistor measurement	Quick capacitor measurement (measures 1mF in 4 seconds)
Overload alarm	Diode/continuity buzzer
LCD backlight	Data hold/Auto power off
2m drop proof	Low power consumption and auto power saving function

### Characteristics

Standard accessories	Batteries, test leads, temperature probe (UT136C+), English manual
Power	1.5V battery (R6) x 2
Display	56.5 x 36mm
Product size	175 x 83 x 53mm
Product net weight	330g
Standard individual packing	Gift Box
Standard quantity per carton	30pcs
Standard carton measurement	390 x 355 x 355mm
Standard carton gross weight	14.8kg